

## Product Sheet TEX 33 LF.CA

## Pneumatic stapler for efficient work. Single release with the finger.

Pneumatic stapler ready mounted on an anodized aluminium plate with pressure reducer, hoses and fittings, as well as an infinitely adjustable aerial valve for individual triggering with the finger. Suitable for all common textile applications, such as stapling facing, stapling sleeve slits and side slits, stapling care and production labels, stapling rear facing edge, stapling breast pocket placket and placket on sleeve hole, etc.

## Techn. Details: TEX 33 LF.CA

Product category	Clothing & Textile » Closed stitching
Loading capacity	1 staple strip (approx. 290 staples)
Mouth width	1,4 cm
Insertion depth	12,5 cm
Staple Type	Closed
Weight	4,0 kg
Operating pressure	4 bar
Bracket type	SITEX 33/5D SITEX 33/6D SITEX 33/8D SITEX 33/6C SITEX 33/8C

Special accessories:

Extended projection available in 19, 25 and 35 cm



**ANKER-TEX** Industrial staplers and

staples

ANKER-TEX GmbH Dietkircher Str. 3 D-65551 Limburg Tel. +49 (0)6431-2121 4811 Fax. +49 (0)6431-2121 4829 E-Mail: sales@anker-tex.de